Annual Water Quality Report

SUCCESS LAKE

Water Year 2002



Written by
John J. Baum
Water Quality Engineer
U. S. Army Corps of Engineers
Sacramento District
January 2003

TABLE OF CONTENTS

- I Purpose of this report
- II Brief history of Success Lake
- III Summaries for this year's sampling events
- IV Conclusions
- V References
- VI Appendices
 - A. Basic definitions of lake water quality terms.
 - B. Profile Data and charts (S.D., Temp., DO, and pH).
 - C. Phytoplankton data and charts
 - D. Soluble metals data and charts
 - E. Inorganic sample data
 - F. MTBE table of results
 - G. Fish tissue analysis table

Success Lake

I. Purpose

This report is part of an environmental monitoring program that began at Success Lake in April 1974. The monitoring program was implemented to determine the level of water quality in the lake for both recreation and environmental health and to satisfy the Department of Army Engineering Regulation 1110-2-8154, "Water Quality and Environmental Management for Corps Civil Works Projects".

II. Brief Description of Success Lake

Success Lake is located in southern central California, 8 miles east of Porterville. The lake is nestled in the southern Sierra Nevada foothills and is surrounded by grasslands and blue oaks. The lake was formed by the construction of a dam on the Tule River that was completed in 1962. The dam is 142 feet high and 3,490 feet across. During the spring run-off season it stores 82,000 acre-feet of water and has a water surface area of 2,450 acres. Since being built by the US Army Corps of Engineers for flood control and irrigation, the lake has become a popular destination for recreation. Summers are warm and the winters mild, allowing for year-round activities.

Generally there are two sample events a year, spring (April) and late summer (August). Since the start of the monitoring program, a water quality report is produced yearly to list results and address any concerns of the previous water year.

Generally Success Lake has a depth of < 100 ft during the sampling events, and is considered a eutrophic (nutrient rich) lake when characterized by its clarity. One of the common characteristics of a eutrophic lake such as Success Lake is that during warm late summer months the bottom depths are low in dissolved oxygen (DO). Additionally Success Lake is warm (>20°C) in the late summer. Due to both the low DO concentrations and high temperatures, warmwater fish species are best suited to survive in the lake. Warmwater fish species include bass, carp, perch, bluegill, crappie, and catfish. Another characteristic of eutrophic (nutrient rich) lakes is their low water clarity due to algal blooms and sediments suspended by wind action. Water clarity is often measured in terms of Secchi Disc depth or SD (Appendix A). Historically the water clarity in Success Lake has been low (Average SD = 5.34 feet), but 88.5 % of the samples have met the recreational goal of 4 feet or greater (Figure 1). In 2001 both the spring and the late summer Secchi Disc depth measurements were above the goal of 4 feet (2001 Spring SD = 4.5 feet and 2001 Late Summer SD = 4.25 feet).




Figure 1. Historical Secchi Depth Values at Success Lake (2002 values included).

The 2001 Water Quality Report listed MTBE levels and dissolved oxygen depletion as areas of concern, and dismissed high concentrations of dissolved iron as being due to isolated to lake bottom samples. While concentrations of MTBE in the spring of 2001 were just above the detection limit of 2 ppb (2001 MTBE Spring = 3 ppb), values were found to be higher during the summer. Concentrations of MTBE near the marina and in the center of Success Lake were 6 ppb.

III. Sample Summaries for this year.

Introduction

The following general summaries are split into their respective sample types. Each type of sample summary includes a discussion of both the spring (April) and late summer (August) samples to better examine trends within the current year. The types of parameters monitored this year include: Secchi Disc depths, water column profiles (temperature, DO and pH), phytoplankton characterization, metals concentrations, MTBE concentrations, Inorganic characterization (alkalinity, phosphorous, nitrogen, etc..), and fish mercury concentrations. For a more detailed explanation of the importance for each type of sample, please see Appendix A.

SECCHI DEPTH

The Secchi Disc depth found during the spring and late summer sampling were similar to previous events. Traditionally the lake varies in its clarity. More often the clarity is better in the spring than in the late summer, but sometimes the late summer is clearer. In spring the water clarity was higher and had a SD of 9.5 feet. The spring SD was the second highest value recorded for Success Lake since beginning the monitoring program. The clarity of Success Lake was highest in spring 2000 (Spring 2000 SD = 10.75 feet). The late summer SD of 5 feet was above the recreational goal of 4 feet and an improvement from last year (Summer 2001 SD = 4.25) (Appendix B).

TEMPERATURE VALUES

The temperature profiles for Success Lake are indicative of a seasonally well-mixed lake. The lake is well stratified in the spring, but the layers disappears by the warm temperatures of late summer. The difference in the depth of the lake between the spring and late summer sampling events was considerable (spring depth = 72.2 feet, late summer depth= 52.5 feet). The average temperatures also were very different (spring average temp. = 13.88 °C, late summer average temp.= 25.10 °C) at each sampling event. Success Lake's temperature varies due to its not having a deep-water area to buffer it from the warm summer air temperatures. Due to the warmth of the water, Success Lake may not be able to support coldwater fish species year round. For detailed results obtained during the sampling events, please see Appendix B.

DISSOLVED OXYGEN

The dissolved oxygen (DO) concentration in the lake differs greatly from spring to late summer. In the spring DO concentrations were 7.83 mg/l DO near the surface (@ 1 foot depth) and 3.82 mg/L at the bottom of the lake (72.2 feet). DO concentrations in the late summer are much lower and have a steady gradient from near the surface (DO = 4.40 mg/l @ 1 foot depth) to the bottom of the lake (DO =0.49 mg/l @ 52.5 foot depth). The low DO values at the bottom of the lake are associated the decomposition of waste materials at accelerated rates due to the warm temperatures. Fish species that require greater than 5 mg/l DO at cooler water temperatures (< 20°C) would be unlikely to survive year round in Success Lake. For detailed results obtained during the sampling events, please see Appendix B.

PH LEVELS

At the spring sample event pH values in the lake were slightly basic (pH = \sim 7.22) throughout the water column. The pH values in the late summer profile varied widely. The pH was more basic towards the surface and middle waters (max pH = 7.86) and slightly acidic at the bottom (pH = 6.78). The lower pH values at the bottom of the lake increase the likelihood that higher soluble metal concentrations will be in lake bottom samples. For detailed results obtained during the sampling events, please see Appendix B.

PHYTOPLANKTON

In the spring sample, the algal biomass within the lake was much higher (Biomass = $2083.05 \ \mu g/L$) when compared to spring 2001 (2001 Spring biomass = $427.49 \ \mu g/L$). In spring 2001 diatoms were the most dominant species, but in spring 2002 dinoflagellates were the dominant species. In late summer the same trend occurred and the phytoplankton population was much lower in summer 2001 (2001 Summer Biomass = $429.02 \ \mu g/L$) than summer 2002 (Biomass = $3531.12 \ \mu g/L$). Diatoms were the most dominant species during the 2002 and 2001 late summer sampling events. For detailed results obtained during the 2002 sampling events, please see Appendix C.

METALS

Several metals exceeded their applicable criteria during either the spring or summer.

Iron and manganese in summer lake bottom samples were above secondary MCL's that

are based on aesthetics, but iron exceeded even fish criteria. Selenium in a late summer sample of water flowing into the lake also exceeded the fish criteria (5 ppb), although ambient lake values were lower. For detailed results obtained during the sampling events, please see Appendix D.

Dissolved iron concentrations in Success Lake have been historically high. While samples generally don't exceed the secondary MCL (300 ppb) or the instantaneous maximum fish criteria (1000 ppb), the late summer 2002 lake bottom iron concentration (1700 ppb) did exceed both limits. There are no results for spring lake bottom concentrations, but the concentrations of both of the lake inflows (South Fork Tule River and the North Fork Tule River) were elevated (100 ppb and 60 ppb).

In late summer 2002, water at the bottom of the lake had a manganese concentration of 460 ppb. This was the highest manganese concentration since the summer bottom sample in 2000 (660 ppb). The concentration was above the secondary Maximum Contaminant Level (MCL manganese = 50 ppb). Exceeding the secondary manganese MCL is not seen as an area of concern due to it being based on aesthetic preferences rather than health effects.

Selenium was found at an elevated concentration in the North Fork of the Tule River (just upstream of Success Lake) during the late summer sampling event. The river sample had a selenium concentration of 6 ppb, which is greater than the fish criteria limit (5 ppb) but far less than the MCL (50 ppb). In the last five years of sampling (1998 –

2002, twice a year) only two samples have shown elevated concentrations of selenium and both were from the same location, North Fork of the Tule River. The Tule River sampling site will be monitored closely in 2003.

MTBE

Concentrations for MTBE around the lake were found to be 4 ppb during the spring but increased in late summer sampling to a maximum of 12 ppb near the dam very nearly equaling the California MCL for this substance. The spring 2002 results were close to the MTBE concentrations found during both spring and late summer sampling events in 2001 (4-5 ppm). In late summer 2000 the concentrations of MTBE in the lake were 9 ppm, which is more similar to the 2002 results. For detailed results obtained during the sampling events, please see Appendix F.

INORGANIC ANALYSIS

Results for the spring and late summer inorganic analysis were within historic and expected ranges, and the only parameters to note are the alkalinity, chloride, and total solids concentrations in waters flowing into the lake during the summer. For detailed results obtained during the 2002 sampling events, please see Appendix E.

The alkalinity results for inflowing water samples in Spring (50 mg/L CaCO3) and Summer (180 mg/L CaCO3) at Success Lake indicated a dramatic increase. The 2002 summer lake inflow sample had the highest alkalinity concentration of all the lakes monitored by the USACE for the last three years.

The chloride concentration of water flowing into the lake was 22 mg/L compared to 2 mg/L seen in the spring sample. Concentrations of chloride in the lake during the spring and summer 2002 sampling events were 4 mg/L and 8 mg/L respectively.

The total solids in the lake were characteristically high during the summer sampling event (170 mg/L), but the total solids concentration in water flowing into the lake during the summer were higher than expected at 280 mg/L.

FISH TISSUE ANALYSIS

Fish tissue analysis for total mercury was performed on a composite sample composed of tissue from three small mouth bass collected in April 2002. The composite sample had a resulting total mercury concentration of 0.18 ppm. This is below both the U.S. F.D.A. criteria for a fish advisory (1 ppm) and the California Office of Environmental Health Hazard Assessment (OEHHA) screening value to continue monitoring (0.3 ppm). The 2002 composite sample had a lower mercury concentration than the 2000 event (0.32 ppm) and the 2001 (0.29 ppm) composite sample. For detailed results obtained during the sampling events, please see Appendix G.

IV. Conclusions

Success Lake is a moderately eutrophic lake that can support warmwater fish species.

Coldwater fish that require temperatures below 20 C and dissolved oxygen concentrations greater than 5 mg/L may have difficulties surviving year round at Success Lake.

Contaminants of concern in Success Lake for 2002 are dissolved iron and MTBE during summer conditions which is in a premonitory status. There are also concerns about the concentration of dissolved selenium, chloride, and total dissolved solids in water flowing into the lake during the summer. Additionally the concentration of dissolved oxygen in the lake is low year round. For the summer 2002 sampling event no part of the water column was above the recommended 5 mg/L DO concentration.

V. References

- North American Lake Management Society (1990). *Lake and Reservoir Restoration Guidance Manual*, EPA 440/4-90-006, U.S. Environmental Protection Agency, Washington, DC.
- Novotny, V., and H. Olem (1994). *Water Quality: Prevention, Identification, and Management of Diffuse Pollution*, Van Nostrand Reinhold, New York, New York.
- Tchobanoglous, G., F. L. Burton, and H. D. Stensel (2003) *Wastewater engineering:* treatment and reuse / Metcalf & Eddy, Inc., McGraw-Hill, Boston, MA.
- Welch, E.B. (1992) *Ecological Effects of Wastewater: Applied limnology and pollutant effects*, Chapman and Hall, Cambridge University Press, Great Britain.
- Wetzel, R.G. (1975). Limnology, W.B. Saunders Company, Philadelphia, PA.

VI. Appendices

Appendix A: Glossary of Sample Types

Glossary of Sample Types

This glossary of sample types is intended to provide a general background and indicate the importance of each sample in determining water quality. These are meant to be brief and basic. If a further explanation is desired please refer to the list of references provided in this report.

Secchi Depth

One of the oldest and easiest methods to determine lake clarity is the Secchi depth (SD). The Secchi depth is determined by dropping a Secchi disc into a water body and determining the depth that it is last visible from the surface of the water. Secchi discs are generally white and 20 cm in diameter. Secchi depth values are most impacted by the light intensity at the time of sampling and the scattering of light by solid particulates within the water column. Algal growth (phytoplankton) and sediment re-suspension are often major constituents of solid particulates within the water column. Secchi depth values can be used to estimate the Trophic state or the nutrient levels within the lake. The more nutrients are available, the larger likelihood of algal blooms that limit water clarity. Due to recreational concerns for safety, the goal for Secchi depth values is four feet or greater.

Temperature Profiles and Data Points

The temperature profile of a lake provides information how a lake is operating and the potential for aquatic biota to live within the lake. The temperature profile is a direct indicator if a lake is stratified. Stratification in lakes is created generally by temperature affecting the density of water molecules. Stratification is usually indicated by a region of similar temperature nearer the surface of the water (epilimnion), then a region of temperature transition (metalimnion), to another layer of nearly constant temperature at the bottom of the lake (hypolimnion). Each layer in a stratified lake is important, but the existence of a hypolimnion can drastically impact how well a lake can handle warmer temperatures such as those found in northern California during the summer. The hypolimnion acts as a buffer against large temperature shifts. The nature of dam operation is that water is discharged near the bottom, releasing the hypolimnion, and eliminating stratification. This operation limits the ability of reservoirs to regulate their temperature during the summer months. Stratification isn't always desirable. When a lake isn't stratified and is instead well mixed, the required nutrients near the bottom of the lake become available to phytoplankton for growth. Temperatures within lakes also indicate which species of fish will survive within a lake. Coldwater species of fish require temperatures below 20 degrees C in order to spawn and survive. If a lake is often above 20 degrees C, then only warmwater fish species will survive.

Dissolved Oxygen (DO) Concentration Profiles

DO is required by organisms for respiration and for chemical reactions within lake waters. The recommended level for DO for most aquatic species survival is 5mg/L. In lakes, biota waste (detritus) falls to the bottom of the lake to be utilized by bacteria. The

bacteria need oxygen and will deplete levels near the bottom of a lake, especially during warm temperature, high respiration conditions. For nutrient rich (eutrophic) lakes more organisms will grow, create wastes, and cause oxygen depleted regions at the lowest areas. Under these conditions only aquatic species that can survive low DO conditions in warm water near the surface will survive.

PH Profiles

The pH profiles of the lakes indicate the potential for certain chemical reactions to occur. In high pH (greater than pH = 7 or basic) aquatic systems, metal pollutants tend to form into insoluble compounds that fall onto the lake floor. In low pH (less than pH = 7 or acidic) systems or areas metal ions become soluble and available for uptake into aquatic organisms. Other compounds like ammonia that are introduced into a low pH aquatic environment will transform into soluble nitrate and be utilized by organisms.

Phytoplankton Analysis

Phytoplankton analysis indicates the health, nutrients, and biodiversity within a lake. Lakes that have few nutrients available (Oligotrophic) will generally have a much lower quantity of phytoplankton (high Secchi depth) but the number of phytoplankton species seen will be large. In a lake that is nutrient rich (eutrophic) there are generally large phytoplankton blooms (low Secchi depth), but they are made up of a couple of phytoplankton species. Certain species of phytoplankton are preferred food sources for zooplankton (small invertebrates). Generally species like diatoms and green algae can be consumed by the filter-feeding zooplankton, but species like bluegreen algae are low in nutrients and are difficult to consume. Some species like the dinoflagellates can grow horn like points to discourage potential predators. In nutrient rich waters where there is plenty of phosphorous, nitrogen can be limited for biological growth. While most species can't grow due to the lack of nitrogen, bluegreen algae (cyanobacteria) have the ability to utilize nitrogen from the atmosphere when required. This gives bluegreen algae the ability to dominate in many eutrophic lakes.

Soluble Metals Analysis

The soluble metals analysis indicates the exposure of humans and aquatic organisms to toxic metals. These metals often build up as they are consumed through the food chain. Water samples provide an indicator for additional problems. Soluble forms of metal ions are more prevalent in low pH (pH <7, or acidic) environments.

MTBE Analysis

MTBE (methyl tertiary-butyl ether) is a chemical additive to gasoline to improve combustion. Due to its high solubility, MTBE travels and blends into aquatic systems rapidly. While not found to be extremely hazardous at low levels, the offensive smell and taste is detectible by humans at extremely low concentrations. The effect of MTBE on humans and aquatic systems is still under investigation.

Inorganic Analysis

Alkalinity

Alkalinity is measured in terms of mg/L of calcium carbonate. It indicates a lakes ability to buffer incoming acidic pollution and situational changes.

Ammonia

Ammonia is a gas that is toxic to fish and is more visible at a higher pH. Ammonia is created through anthropogenic inputs, bacteria cell respiration, and the decomposition of dead cells. Due to being a gas, given time ammonia will volatilize from the water. At a lower pH, much of the ammonia is converted to ammonium (a nutrient for root bound plant life) and utilizes DO in the nitrification process.

Chloride

The chloride ion is an indicator of any salinity increases within a lake. Most fresh water aquatic species are sensitive to salinity changes.

Nitrate

Nitrate is the nitrogen product created through the nitrification of ammonium. Nitrate is a soluble form of the nutrient nitrogen and is utilized by phytoplankton.

Total Phosphorous

The total phosphorous provides a measure of both utilized and soluble phosphorous within water samples. Phosphorous is a required nutrient for plant growth and development.

Ortho Phosphorous

Ortho phosphorous is the soluble form of phosphorous that is utilized by free-floating aquatic plants (phytoplankton).

Kjeldahl N

Kjeldahl nitrogen or total Kjeldahl nitrogen (TKN) is a measure of the total concentration of nitrogen in a sample. This includes ammonia, ammonium, nitrite, nitrate, nitrogen gas, and nitrogen contained within organisms.

COD

Chemical Oxygen Demand (COD) is a measure of the total oxygen required to complete the chemical and biological demands of a sample.

Fish Tissue Analysis

Fish tissue is analyzed to examine potential exposure of humans to toxicants as well as the health of the aquatic food chain. In aquatic systems toxic contaminants can build up (or bioaccumulate) within animals at the top of the food chain. Contaminants (especially organic pollutants) are retained within the fat tissue of an organism, therefore in fish samples the lipid content is often measured.

Lake Code Designation

Laboratory Reports are provided in the previous sections.

Sample ID is "XX-YY-ZZ" where


NH for New Hogan PF for Pine Flat SO for Sonoma SU for Success

ZZ designation XX designation: YY designation BB for Black Butte SP for Spring S for surface of Lake SU for Summar B for bottom of Lake EA for Eastman EN for Englebright I-1 for inflow1 HE for Hensley I-2 for inflow 2 IS for Isabella O for outflow KA for Kaweah ME for Mendocino MC for Martis Creek


Example: BB-SU-S is for a water sample taken from Black Butte in the Summer on the Lake's Surface.

Appendix B: Profile Data and Charts (Secchi Disc, Temperature, DO, and pH)


Lake Success - Temperature Profile



Lake Success - Dissolved Oxygen Profile



Lake Success - pH Profile




		SUC	CESS					
Sample Loca	tion: Behind	dam		Date: 4/17/02	2			
Observers:Ti	m McLaughlin	ļ		Time: 2:00 p	m			
Lake Elevati	on: 678.29							
		Weather C	Conditions:					
Wind Speed (mph):5 Precipitation: 0.3 Temp (F): 65								
SECCHI Dep	th: 9 feet and	6 inches						
Depth-M	Depth-F	Temp-C	Cond	DOm g/L	pН			
21.5	72.2	9.94	205	3.82	7.15			
20	65.6	10.01	205	4.51	7.18			
18	59.1	10.40	202	5.25	7.19			
16	52.5	10.56	199	5.52	7.21			
14	45.9	11.27	195	6.40	7.26			
12	39.4	11.59	187	6.46	7.26			
10	32.8	12.15	168	6.58	7.20			
8	26.2	15.68	167	6.87	7.21			
6	19.7	18.43	168	7.92	7.24			
4	13.1	18.75	169	8.05	7.26			
2	6.6	18.86	172	7.87	7.24			
0.03	1	18.93	172	7.83	7.22			
SOUTH FOR	K TULE (Inflo	w)						
Temp (F)	pН		DOmg/L	EC	Flow rate (cfs			
55.6	7.27		-	-	45			
NORTH FOR	K TULE (Inflo	ow)	-	-				
Temp (F)	pН		DOmg/L	EC	Flow rate (cfs			
55.2	7.42		-	-	-			
VISUAL OBS	ERVATIONS:	-	-	-	<u> </u>			


		SUC	CESS					
Sample Loca	tion: Behind	dam		Date: 8/21/02	2			
Observers:Ti	m McLaughlin	1		Time: 2:00 pm				
Lake Elevati	on: 597.05			•				
		Weather C	Conditions:					
Wind Speed	(mph):15	Precipitation	n: 0	Temp (F): 80)			
SECCHI Dep	th: 5 feet	•		•				
Depth-M	Depth-F	Temp-C	Cond	DOm g/L	pН			
15.8	52.5	16.92	291	0.49	6.78			
14	45.9	20.04	256	0.48	6.86			
12	39.4	25.01	249	0.61	7.13			
10	32.8	26.80	246	0.74	7.25			
8	26.2	26.98	246	1.01	7.28			
6	19.7	27.10	246	2.10	7.40			
4	13.1	27.37	244	3.73	7.69			
2	6.6	27.58	244	4.21	7.78			
0.03	1	28.06	243	4.40	7.86			
SOUTH FOR	K TULE (Inflo	ow) - DRY						
Temp (F)	pН		DOmg/L	EC	Flow rate (cfs			
-	-		-	-	-			
NORTH FOR	K TULE (Inflo	ow)						
Temp (F)	pН		DOmg/L	EC	Flow rate (cfs			
76.8	7.54		-	-	-			
VISUAL OBS	ERVATIONS:	Slight hydroge	en sulfide smel	1.				


Appendix C: Phytoplankton Data and Charts


Phytoplankton Biomass 2002 Success Lake





Appendix D: Metals Data and Charts


























Appendix E: Inorganic Sample Data

	Inorganic Results (mg/L) For surface lake waters (spring)											
	ВВ	EA	EN	HE	IS	KA	MC	ME	ИН	PF	SO	SU
Alkalinity		60	40	50	60	30	40	70	80	20		100
Ammonia		<0.1	0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1		<0.1
Chloride		21	2	21	4	4	3	<1	6	5		4
Nitrate		<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	0.2	<0.1		<0.1
Total P		<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1		<0.1
Ortho P	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1		<0.1
Sulfate		5.3	2.6	4.2	8.9	2	1	8.2	9	2.1		4.7
Kjeldahl N		0.6	0.1	0.4	0.2	<0.1	0.3	0.2	0.2	0.2		<0.1
COD					<50							
Tot Solids		120	70	100	110	60	78	100	120	21		150

Ir	Inorganic Results (mg/L) For inlet waters to the lakes (spring) (I-1 only)											
	ВВ	EA	EN	HE	IS	KA	MC	ΜE	ИН	PF	SO	SU
Alkalinity	100	70	40	50	20	30	40	80	90	10	100	50
Ammonia	<0.1	<0.1	<0.1	<0.1	<0.1		0.1	<0.1	<0.1	<0.1	<0.1	<0.1
Chloride	13	25	3	21	<1	<1	4	<1	6	4	3	2
Nitrate	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	0.1	<0.1	<0.1	<0.1
Total P	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
Ortho P	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	0.2	
Sulfate	18	2.1	2.3	3	2.8	1.9	0.8	8.8	11	1.6	11	3.5
Kjeldahl N	<0.1	0.2	<0.1	0.3	<0.1	<0.1	0.2	0.2	0.1	0.1	0.1	<0.1
COD	<50	<50	<50	<50	<50	<50	<50	<50	<50	<50	<50	<50
Tot Solids	170	130	59	110	60	60	90	110	150	30	130	90

	Inorganic Results (mg/L) For surface lake waters (summer)												
	BB	EA	EN	ΗE	IS	KA	MC	ME	ИН	PF	SO	SU	
Alkalinity	140	70	40	50	50	40	70	90	80	10	80	110	
Ammonia	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	0.1	<0.1	<0.1	0.1	<0.1	
Chloride	16	26	4	19	6	5	5	5	9	3	5	8	
Nitrate	<0.1	1.5	<0.1	1.3	0.7	<0.1	<0.1	<0.1	<0.1	0.6	<0.1	<0.1	
Total P	<0.1	0.3	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	
Ortho P	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	
Sulfate	16	4.1	3.6	3.5	5.9	2	0.7	7.4	14	1.6	6.4	4.4	
Kjeldahl N	<0.1	2.7	<0.1	0.4	0.4	0.3	<0.1	0.2	<0.1	<0.1	0.2	0.6	
COD	<50	60	<50	<50	<50	<50	<50	<50	<50	<50	<50	<50	
Tot Solids	200	190	50	120	98	80	80	120	120	52	100	170	

In	Inorganic Results (mg/L) For inlet waters to the lakes (summer) (I-1 only)											
	ВВ	EA	EN	HE	IS	KA	MC	ME	ИН	PF	SO	SU
Alkalinity	150	90	40		60	40	80	100	130	20	110	180
Ammonia												
Chloride	16	490	5		10	8	3	5	14	4	5	22
Nitrate												
Total P												
Ortho P												
Sulfate	16	4.5	3		9.8	3.2	<0.5	6	14	2.7	5.4	8.7
Kjeldahl N												
COD												
Tot Solids	200	1300	50		140	100	100	150	200	50	140	280

Appendix F: MTBE Table

2002 MTBE Results Units are ug/L (ppb)

The following table provides an overview of the lab results for the 2002 MTBE $\,$

monitoring program.

momitoring	F8	_,							
Lake	Spring	Spring	Spring	Spring	Summer	Summer	Summer	Summer	Remarks
	S	S-1	S-M	S-C	S	S-1	S-M	S-C	
Black Butte	2		2		<2		<2		
Eastman	5				<2				
Englebright	3		3		10		10	10	
Hensley	3		3		3		3		
Isabella	<2	<2	<2	<2	<2	<2	<2	<2	
Kaweah	2		2	<2	8		6	6	
Martis Cr.	<2				<2				
Mendocino	<2				<2				
New Hogan	<2				3				
Pine Flat	<2		<2		2		2		
Sonoma		3	<2		<2		2		
Success	4		4	4	11	12	11	11	

Notes:

- 1. Non-Detect is indicated by "<2" since the Reporting Limit is 2 ppb or 0.002 ppm.
- 2. No enforceable acceptance criteria has been established for MTBE. See EPA Fact sheet.
- 3. Maps are provided to illustrate the sampling locations for samples: S / S-1, S-M, and S-C. Sample S and sample S1 are located near the dam; sample S-M is located within 50 ft of the Marina; and sample S-C is located near the center of the lake.
- 4. For 2002, the number of MTBE water sampling at each lake is based on last year's lab results.
- 2 samples were taken from Eastman, Martis Creek, Mendocino, and New Hogan because MTBE was historically non-detectable. The 2002 results of non-detectable levels were similar except Lake Eastman and New Hogan now reported low, detectable levels of MTBE.
- 6. 4 samples were taken from Black Butte, Hensley, Pine Flat and Sonoma because of historically low detectable levels of MTBE.
- 7. 6 to 8 samples were taken from Englebright, Isabella, Kaweah and Success because of historically higher MTBE being found. The 2002 results were similar except Isabella now reported non-detectible levels.
- 8. In 2001, very high MTBE levels were reported at Lake Isabella during the Spring (18 ug/L near the marina). During Spring 2000, Lake Isabella reported 21 ug/L. The 2002 results indicate that the previous MTBE problem near the marina was not visible during the Spring 2002 sampling event, and may have been rectified.

G. Fish tissue analysis table

2002 Fish Tissue Results

The following table provides an overview of the lab results for the 2002 fish tissue program. N/A indicates data is not available due to lack of fish collection. Sample Preparation, filleting and Extraction were in accordance with EPA 823-R-95-007, Sep 95, Volume 1, Section 7.2 (Guidance for Assessing Chemical Contaminant Data for Use in Fish Advisory) which requires the following: Only the edible portion of the fillet shall be analyzed (i.e no skin, tail, fin, head). Tissue digestion shall be accomplished by adding concentrated nitric acid and heating the tube in an aluminum block to reflux the acid. The digestate shall be cooled, diluted to a final volume of 25 ml and analyzed by CVAA. The laboratory conductng the preparation and analysis was Toxscan, Inc in Watsonville, CA and the laboratory mercury analysis was in accordance with CVAA per EPA 7471. The Percent Lipids were per EPA 1664. The FDA criteria for a fish advisory is 1 ppm. The California OEHHA's action level to continue fish tissue monitoring is 0.3 ppm.

Lake	Type of Fish	Type of Analysis	Date	Percent	Mercury	FDA
		(number of fish)	collected	Lipids	Total	Criteria
					ppm	
Black Butte	Sm M Bass	Composite (3)	6/12/02	0.24	0.26	1 ppm
Eastman	Note 4					< Mon 00
Englebright	Note 5	N/A	N/A	N/A	N/A	
Hensley	Black Bass	Composite (3)	4/23/02	< 0.10	0.72	1 ppm
Isabella	Black Bass	Composite (3)	6/4/02	0.20	0.21	1 ppm
Kaweah	Sm M Bass	Composite (3)	7/14/02	0.11	0.53	1 ppm
Martis Cr	Note 4					< Mon 00
Mendocino	Note 6	N/A	N/A	N/A	N/A	
New Hogan	Lg M Bass	Single (1)	6/3/02	< 0.10	0.34	1 ppm
Pine Flat	Note 4					< Mon 01
Sonoma	Note 6	N/A	N/A	N/A	N/A	
Success	Black Bass	Composite (3)	4/15/02	< 0.10	0.18	1 ppm

Notes:

- 9. Non-Detect is indicated by "<0.02". The lab Detection Limit for mercury is 0.02 ppm.
- 10. Total Mercury was reported in mg/g or ppm.
- 11. Total Mercury was conducted instead of Methyl Mercury since EPA 832 allows Total Mercury analysis for an initial screening program. When specific problem areas are identified, methyl mercury analysis are normally performed later as part of the actual health risk assessment.
- 12. The fish tissue program was terminated at Eastman and Martis Creek in 2001 and in Pine Flat in 2002 due to low total mercury results. In 2000, the total mercury was only 0.089 ppm for Eastman (Catfish) and the total mercury was <0.02 ppm for Martis Creek (Brown Trout). For Pine Flat total mercury was 0.21 ppm in 2000 (composite of three Sacramento Sucker fish) and 0.23 in 2001 (composite of three spotted bass).
- 13. Due to seasonal conditions, a fish could not be successfully collected at Lake Englebright. Another attempt will be accomplished for the 2003 report.

14. Fish were not collected at Mendocino or Sonoma due to communication difficulties.

The above 2002 total mercury results indicate only Hensley is higher than average. However, in 2001, the total mercury results were only 0.30 ppm for Hensley (small mouth bass). The 2003 fish tissue program should provide additional data. EPA fact sheet on fish advisories (EPA-823-F-99-016) indicates that the mean average mercury results from numerous lakes in the Northeast United States were found to be 0.46-0.51 ppm for largemouth bass and 0.34-0.53 for smallmouth bass.